



Gas Furnaces

80PS Upflow / Horizontal 80% Furnace

Model #	Input BTU/h (kW)	Heating Capacity BTU/h (kW)	Dimensions (wxhxd) Inches	Cooling CFM	Motor HP (Speed Type)
80PS05EAR01	50,000 (15)	41,000 (12)	14x28 1/16x34	1,200	1/2 (4 PSC)
80PS07EBR01	75,000 (22)	60,000 (18)	17 1/2x28 1/16x34	1,200	1/2 (3 PSC)
80PS10ECR01	100,000 (28)	80,000 (23)	21x28 1/16x34	1,845	1/2 (3 PSC)
80PS12EDR01	125,000 (37)	99,000 (29)	24 1/2x28 1/16x34	2,115	3/4 (3 PSC)
80PS15EDR01	150,000 (44)	119,000 (35)	24 1/2x28 1/16x34	2,080	3/4 (3 PSC)

Quiet operation due to unique solid door design. Stainless and aluminized steel patented heat exchanger for maximum corrosion resistance. Low 34" profile is lighter and easier to handle and allows for optional equipment. Convertible from upflow to horizontal left or right without field conversion. Left or right side gas and electric inlet connections allow for quick and simple change. Direct spark ignition with remote sense, which features an integrated board with an electronic air cleaner hookup. Prepainted galvanized steel cabinet. One of the quietest furnaces on the market today due to a slow-open gas valve and a specially designed draft inducer motor. Grab holes in the doors aid in easy door removal and replacement.

Accessories	Description
RXGF-DA	Internal Filter Rack for Bottom or Side Return
RXGF-CA	Side Return Filter Rack
RXGF-CB	Bottom Return Filter Rack for Upflow Application
RXPF-F01, F02	Fossil Fuel Kit
RXGP-F03	Twinning Kit
RXGR-C14B, C17B, C21B, C24B	Return Air Cabinet

Warranty Information

Gas Heat Exchanger Limited Warranty - Twenty (20) Years
Any Other Part - Five (5) Years

