



Gas Furnaces

90RS 90% High Efficiency Upflow

Model #	Input BTU/h (kW)	Heating Capacity BTU/h (kW)	Dimensions (wxdxh) Inches	Cooling CFM	Motor HP (Speed Type)
90RS04EES01	45,000 (13.19)	42,000 (12.31)	17 1/2x28 1/16x34	1,195	1/2 (4 PSC)
90RS06EES01	60,000 (17.58)	56,000 (16.41)	17 1/2x28 1/16x34	1,100	1/2 (3 PSC)
90RS10EGS01	105,000 (30.77)	97,000 (28.43)	21x28 1/16x34	1,810	3/4 (3 PSC)
90RS12EHS01	120,000 (35.17)	113,000 (33.12)	24 1/2x28 1/16x34	1,900	3/4 (3 PSC)

Low 34" profile is light and easy to handle and leaves room for optional equipment. Left or right side gas, electric, and condensate connections. Integrated control board manages all operational functions and provides accessory hookups for an electronic air cleaner. It is one of the quietest furnaces on the market today due to a slow-opening gas valve and a specially designed inducer system. Prepainted galvanized steel cabinet. Control board diagnostics. Optional indoor or outdoor combustion air.

Accessories	Description
RXGY-E03	Concentric Vent Termination Kit
RXGY-D02, D03, D04	Horizontal Two Pipe Termination Kit
RXGY-B01	Condensate Pump Kit
RXGY-A01	Neutralizer Kit
RXPF-F01, F02	Fossil Fuel Kit
RXGR-C17B, C21B, C24B	Return Air Plenum
RXGF-CB	External Bottom Filter Rack
RXGF-CA	External Side Filter Rack
RXGF-DA	Internal Filter Rack for Bottom or Side Return
RXAA-C173, C174, C185, C187, C175, C176, C188, C177, C187	Plenum Adapter
RXGP-F03	Twinning Kit
RXGB-D17, D21, D24	Solid Bottom Kit

Warranty Information

Primary and Secondary Heat Exchanger - Twenty (20) Years
Any Other Part - Five (5) Years

