



Cased Indoor Coils

R22 Model #	R-410A Model #	Capacity BTU/h	Dimensions (wxdxh) Inches	Replacement Pan
B41A36+X3-14HV	B41A36+4X3-14HV	18,000 - 24,000	14x21 1/4x20	PDP13
B41A36+X3-17HV	B41A36+4X3-17HV	18,000 - 24,000	17 1/2x21 1/4x20	PDP16
B06A36+X3-17HV	B06A36+4X3-17HV	30,000 - 36,000	17 1/2x21 1/4x22	PDP16
B06A36+X3-21HV	B06A36+4X3-21HV	30,000 - 36,000	21x21 1/4x22	PDP20
B06A36+X3-24HV	B06A36+4X3-24HV	30,000 - 36,000	24 1/2x21 1/4x22	PDP23
B66A48+X4-21HV	B66A48+4X4-21HV	42,000 - 48,000	21x21 1/4x24	PDP20
B66A48+X4-24HV	B66A48+4X4-24HV	42,000 - 48,000	24 1/2x21 1/4x24	PDP23
B67A60+X5-24HV	B67A60+4X5-24HV	60,000	24 1/2x22x28	PDP23

ARI rated with OEM condensing units. Field thermostatic expansion valve kits for higher SEER requirements. UL94-VO high temperature rated, UV stabilized nylon 6 drain pan. Enhanced louvered fins for increased heat transfer. Second generation rifled copper tubing for superior refrigerant flow and optimum heat transfer. Hairpin protection brackets. Every coil tested to 500 psi and shipped with a dry nitrogen holding charge. Factory swaged line connections.

Accessories	
BEN4-2/3	Expansion Valve Conversion Kit R22 to R-410A (1.5 to 3 Ton)
BEN4-4/5	Expansion Valve Conversion Kit R22 to R-410A (3.5 to 5 Ton)
HDCE43	R-410A Expansion Valve (1.5 to 3 Ton)
HDCE45	R-410A Expansion Valve (3.5 to 5 Ton)
MDP20	21" Wide Metal Drain Pan for Cased Coils
MDP23	24" Wide Metal Drain Pan for Cased Coils

Warranty Information
Defects of material or workmanship under normal use - Five (5) Years from date of manufacture

