



# Unit Heaters

## F Series Gravity Vent

Model #	Heating Input BTUH (Kw)	Thermal Output BTUH (Kw)	Vent Outlet Diameter (inches)	Standard Motor HP	Air Volume CFM	Approximate Shipping Weight lbs (kg)
F-25	25,000 (7.3)	20,000 (5.9)	4 Round	1/50	380	72 (33)
F-50	50,000 (14.7)	40,000 (11.7)	4 Round	1/35	650	79 (36)
F-75	75,000 (22.0)	60,000 (17.6)	5 Oval	1/15	980	88 (40)
F-100	100,000 (29.3)	80,000 (23.4)	6 Oval	1/30	1,250	97 (44)
F-125	125,000 (36.6)	100,000 (29.3)	7 Oval	1/30	1,600	127 (58)
F-165	165,000 (48.4)	132,000 (38.7)	8 Oval	1/20	2,200	149 (68)
F-200	200,000 (58.6)	160,000 (46.9)	8 Oval	1/20	2,800	170 (77)
F-250	250,000 (73.3)	200,000 (58.6)	10 Oval	1/6	3,360	204 (93)
F-300	300,000 (87.9)	240,000 (70.3)	10 Oval	1/4	3,800	221 (100)
F-400	400,000 (117.2)	320,000 (93.8)	12 Oval	1/2	4,940	276 (125)

Orifices for natural gas, aluminized steel heat exchanger, aluminized steel burner rack, manual match lit pilot, single-stage combination gas valve, fan and limit safety controls, energy cut-off device, blocked vent shut-off system, 24 volt control voltage transformer, full safety fan guard. Factory and field installed options are available on special order items.

Accessories	Description
Option AC2	409 SS Heat Exchanger
Option AD2	409 SS Burner
Option AG2	Two-Stage Gas Control
Option AH2	Spark Ignition
Option BF8	Low Ambient Fan Control
Option CD2	25-65 Degree Variable Air Deflection

### Warranty Information

For the original owner-user, the Reznor unit will be free from defects in materials or workmanship. This warranty is limited to twelve (12) months from the date of the original installation, whether or not actual use begins on that date or eighteen (18) months from date of shipment by Reznor, whichever comes first. Extended nine (9) year non-prorated warranty on the heat exchanger, burners, draft hood and flue battle assembly. Extended four (4) year non-prorated warranty on all electrical and mechanical operating components

