



# Commercial Condensing Units

## RAWL High Efficiency Series 6.5 through 20 Tons with R410A

Model #	Gross Cooling Capacity BTU/H (kW)	EER	Sound Rating	Compressors (Stages of Cooling)
RAWL-078CAZ	77,000 (22.6)	11.2	8.6	1
RAWL-090CAZ	90,000-92,000 (26.4-27.0)	11.2	8.6	1
RAWL-120CAZ	117,000-118,000 (34.3-34.6)	11.2	8.8	1
RAWL-150CAZ	146,000 (42.8)	11.1	8.8	2
RAWL-180CAZ	178,000 (52.2)	11.0	8.8	3
RAWL-240CAZ	244,000 (71.5)	10.0	8.8	3

Galvanized steel cabinet with powder paint finish makes the unit durable and protected from the elements. The frame and panel type of construction of the unit allows all access panels to be open or removed without affecting the structural strength of the unit. The condenser coil is protected 100% by stamped louver panels. The Scroll Compressor is hermetically sealed with internal high temperature protection, and durable insulation on motor windings. The entire compressor is mounted on rubber grommets to reduce vibration and noise. Service access panels may be opened or removed without impacting operation. Low/High pressure controls deactivate system if pressure is abnormally high or low. All units are tested at the factory prior to shipments.

Accessories	Description
RXAT-A01	Anti-Short Cycle Timer Kit
RXAG-A048, A020	Sight Glass
RXAV-BD048	Liquid Line Solenoid Valve

Warranty Information
Compressor - Five (5) Years
Any Other Part - One (1) Year

