



Cased Indoor Coils

RCFL R-410A Refrigerant Coils

Model #	Capacity BTU/h	Coil Casing Inches	Dimensions (wxdxh) Inches
RCFL-2414AC	18,000 - 24,000	14	14x21x23 3/16
RCFL-2417AC	18,000 - 24,000	17.5	17 1/2x14 1/2x20
RCFL-3617AC	30,000 - 36,000	17.5	17 1/2x17 7/8x20
RCFL-3621AC	30,000 - 36,000	21	21x17 1/2x20
RCFL-4821AC	42,000 - 48,000	21	21x25 7/8x28
RCFL-4824AC	42,000 - 48,000	24.5	24 1/2x25 3/8x32
RCFL-6024AC	60,000	24.5	24 1/2x30 1/4x32

Coils are constructed of enhanced aluminum fins bonded to inner grooved copper tubing. Coils have sweat fitting refrigerant connections. Coils are ARI certified for a wide application of Rheem outdoor products. Condensate drain pan made of high grade, heat resistant corrosion free thermal-set material. Unique drain pan maximizes application flexibility and condensate removal. Has two sets of 3/4" N.P.T. condensate drain connections for easier connection. Bi-directional airflow eliminates the need to switch internal components from horizontal left to right. Universal duct flanges are included with all models. Coils are tested at the factory with an extensive refrigerant leak check. Ideally suited for new installations or add on air conditioning. Compatible with Germicidal Light System (UV resistant).

Accessories

RXBA-AC, AE	Plenum Adapter
RXHH-A01, A02, A03, A04, A05	Horizontal Adapter Kit

Warranty Information

Coil Leaks due to factory defect - Five (5) Years
Any Part - Five (5) Years



CASED COIL

