



Gas Furnaces

RGFD Classic 90% Plus with Contour Comfort Control Upflow

Model #	Input BTU/h (Kw)	Heating Capacity BTU/h (Kw)	Dimensions (wxdxh) Inches	Cooling CFM Range	ECM Motor HP
RGFD-06EMCKS	60,000 (17.58)	55,800 (16.35)	17 1/2x28 1/16x34	600 - 1,200	1/2
RGFD-07EMCKS	75,000 (21.98)	72,000 (21.10)	17 1/2x28 1/16x34	600 - 1,200	1/2
RGFD-09EZCMS	90,000 (26.38)	86,000 (25.20)	21x28 1/16x34	1,200 - 2,000	1
RGFD-10EZCMS	105,000 (30.77)	100,000 (29.31)	21x28 1/16x34	1,200 - 2,000	1
RGFD-12ERCMS	120,000 (35.17)	115,000 (33.70)	24 1/2x28 1/16x34	1,200 - 2,000	1

Patented heat exchanger provides maximum corrosion resistance. Modulation between 40% - 100% of total capacity. An extremely quiet unit is created through reduced firing ratings, and electrically efficient motor, and solid doors. Has a minimum 94% AFUE and a constant low speed fan. A constant temperature rise provides superior comfort. Seven segment LED for system diagnostics. A diagnostic history helps when troubleshooting is necessary. Includes a two-speed induced draft motor and a direct spark ignition with remote sense. Left/Right side gas and electric inlets and condensate drainage allows for easy change. Optional indoor or outdoor combustion air available. Quiet, efficient ECM motor technology providing nominal air flow to 1.0 inch of external static pressure.

Accessories	Description
RXGY-E03	Concentric Vent Termination Kit
RXGY-D02, 03, 04	Horizontal Two Pipe Vent Termination Kits
RXGY-B01	Condensate Pump
RXGY-A01	Neutralizer Kit
RXGR-C17B, 21B, 24B	Return Air Plenums
RXGF-CB	External Bottom Filter Rack
RXGF-CA	External Side Filter Rack
RXGJ-FP07	LP Kit
RXPF-F02	Fossil Fuel Kit

Warranty Information

Primary and Secondary Heat Exchanger - Limited Life
Any Other Part - Five (5) Years

