



Gas Furnaces

RGGD Prestige Series 90% Plus Modulating Downflow with Contour Comfort Control

Model #	Input BTU/h (Kw)	Heating Capacity BTU/h (Kw)	Dimensions (wxdxh) Inches	Cooling CFM Range	ECM Motor HP
RGGD-06EMCKS	60,000 (17.58)	54,720 (16.03)	17 1/2x28 1/16x34	600 - 1,200	1/2
RGGD-07EMCKS	75,000 (21.98)	69,000 (20.22)	17 1/2x28 1/16x34	600 - 1,200	1/2
RGGD-09EZCMS	90,000 (26.38)	83,160 (24.37)	21x28 1/16x34	1,200 - 2,000	1
RGGD-10EZCMS	105,000 (30.77)	95,865 (28.09)	21x28 1/16x34	1,200 - 2,000	1
RGGD-12ERCMS	120,000 (35.17)	110,880 (32.49)	24 1/2x28 1/16x34	1,200 - 2,000	1

Stainless steel heat exchanger for maximum corrosion resistance and thermal fatigue reliability. Depending on the type of thermostat installed the furnace has either a modulating, two-stage, or multistage function. Ultimate quiet operation due to reduced firing rates, electrically efficient ECM2+ motor, and solid doors. Low speed constant fan. Constant temperature rise for superior comfort. Seven segment LED for system diagnosis. Diagnostic history for troubleshooting. Two-speed induced draft motor. Direct spark ignition with remote sense. Top electrical connections, left or right gas and condensate drainage connections on downflow models.

Accessories	Description
RXGY-E03, D02, 03	Vent Termination Kits
RXGY-B01	Condensate Pump Kit
RXGY-A01	Neutralizer Kit
RXGC-B17, 21, 24	Combustible Floor Bases
RXGF-CC	External Filter Rack
RXGJ-FP07	LP Kit
RXPF-F02	Fossil Fuel Kit
41-24312-04	Programmable Thermostat
41-25347-01	Non-Programmable Thermostat

Warranty Information

Primary and Secondary Heat Exchanger - Limited Life
Any Other Part - Five (5) Years

