



# Gas Furnaces

## RGRL Classic Series 90% Plus with Dual Comfort Control Two-Stage Upflow

Model #	Input BTU/h (Kw)	Heating Capacity BTU/h (Kw)	Dimensions (wxdxh) Inches	Cooling CFM	Motor HP
RGRL-04EMAES	45,000 (13.19)	42,000 (12.31)	17 1/2x28 1/16x34	1,195	1/2
RGRL-06EMAES	60,000 (17.58)	56,000 (16.41)	17 1/2x28 1/16x34	1,100	1/2
RGRL-09EZAJS	90,000 (26.38)	84,000 (24.62)	21x28 1/16x34	1,910	3/4

Two stages of operation saves energy and maintains optimal comfort levels. Furnace operates at 70% capacity for low-heat and 100% capacity for high-heat. Compatible with single or two-stage thermostat. Stainless steel heat exchanger for maximum corrosion resistance and thermal fatigue reliability. Low 34" profile design is lighter and easier to handle and leaves room for optional equipment. Left or right side gas, electric, and condensate drainage connections on upflow models. An integrated control board manages all operational functions and provides hookups for humidifier and electronic air cleaner. One of the quietest furnaces on the market today due to an insulated blower compartment, a slow-opening gas valve and a specially designed inducer system. Prepainted galvanized steel cabinet. Molded permanent filters. Transformer and control fuse protection. Standard solid bottom. Control board diagnostics.

Accessories	Description
RXGY-E03, RXGY-D02, 03	Vent Termination Kits
RXGY-B01	Condensate Pump
RXGY-A01	Neutralizer Kit
RXGR-C17B, 21B, 24B	Return Air Plenums
RXGF-CB	External Bottom Filter Rack
RXGF-CA	External Side Filter Rack
RXPF-F01, 02	Fossil Fuel Kits

Warranty Information
Primary and Secondary Heat Exchanger - Limited Lifetime
Any Other Part - Ten (10) Years Conditional Parts Warranty

