



Gas Furnaces

RGTA Classic 90% Plus Downflow / Horizontal

Model #	Input BTU/h (Kw)	Heating Capacity BTU/h (Kw)	Dimensions (wxhxh) Inches	Cooling CFM	Motor HP (Speed Type)
RGTA-04EMAES	45,000 (13.19)	41,000 (12.02)	17 1/2x28 1/16x34	1,220	1/2 (4 PSC)
RGTA-06EMAES	60,000 (17.58)	56,000 (16.41)	17 1/2x28 1/16x34	1,180	1/2 (4 PSC)
RGTA-07EMAES	75,000 (21.98)	69,000 (20.22)	17 1/2x28 1/16x34	1,150	1/2 (4 PSC)
RGTA-09EZAJS	90,000 (26.38)	84,000 (24.62)	21x28 1/16x34	1,850	3/4 (4 PSC)
RGTA-10EZAJS	105,000 (30.77)	97,000 (28.43)	21x28 1/16x34	1,820	3/4 (4 PSC)
RGTA-12ERAJS	120,000 (35.17)	112,000 (32.82)	24 1/2x28 1/16x34	2,040	3/4 (4 PSC)

Patented heat exchanger provides maximum corrosion resistance. Low profile design is lighter and easier to handle. Left/Right gas, electric and condensate drainage connection available on upflow models. An integrated control board manages all functions and provides hookups. The combination of an insulated blower compartment, slow opening gas valve and inducer system makes the unit extremely quiet. Cabinet is made of pre-painted galvanized steel. Optional indoor or outdoor combustion air. Transformer and control fuse protection. Control board diagnostics and solid bottom.

Accessories	Description
RXGY-E03, 01	Concentric Vent Termination Kits
RXGY-D02, 03, 04	Horizontal Two Pipe Vent Termination Kits
RXGY-B01	Condensate Pump
RXGY-A01	Neutralizer Kit
RXGR-C17B, 21B, 24B	Return Air Plenums
RXAA-C, 171, 172, 173, 174, 175, 176, 177, 185, 187, 188	Premium Downflow Adapters
RXGC-B17, 21, 24	Combustible Floor Base
RXGF-CC	External Filter Rack
RXPF-F01, 02	Fossil Fuel Kits

Warranty Information

Primary and Secondary Heat Exchanger - Limited Lifetime
Any Other Part - Five (5) Years

