



Gas Furnaces

RGTK Classic Series 90 Plus with Dual Comfort Control Two-Stage Downflow / Horizontal

Model #	Input BTU/h (Kw)	Heating Capacity BTU/h (Kw)	Dimensions (wxdxh) Inches	Cooling CFM	Motor HP
RGTK-06EMAES	60,000 (17.58)	56,000 (16.41)	17 1/2x28 1/16x34	1,180	1/2
RGTK-07EMAES	75,000 (21.98)	70,000 (20.51)	17 1/2x28 1/16x34	1,150	1/2
RGTK-07EYBGS	75,000 (21.98)	70,000 (20.51)	21x28 1/16x34	1,625	3/4
RGTK-09EZAJS	90,000 (26.38)	84,000 (24.62)	21x28 1/16x34	1,850	3/4
RGTK-10EZAJS	105,000 (30.77)	97,000 (28.43)	21x28 1/16x34	1,820	3/4
RGTK-12ERAJS	120,000 (35.17)	113,000 (33.12)	24 1/2x28 1/16x34	2,040	3/4

Two stages of operation saves energy and maintains optimal comfort level. Furnace operates at 70% capacity for low-heat and 100% capacity for high-heat. Compatible with single or two-stage thermostat. Stainless steel heat exchanger with tubular construction for maximum corrosion resistance and thermal fatigue reliability. Low 34" profile design is lighter and easier to handle leaving room for optional accessories. Top electrical connections, left or right side gas, and condensate drainage connections on downflow/horizontal models. Integrated control board manages all operational functions and provides hookups for humidifier and electronic air cleaner. One of the quietest furnaces on the market today due to an insulated blower compartment, slow opening gas valve and a specially designed inducer system. Pre-painted galvanized steel cabinet. Molded permanent filters. Transformer and control fuse protection. Control board diagnostics. Condensate drain trap for horizontal/downflow application.

Accessories	Description
RXGY-E03, RXGY-D02, 03, 04	Vent Termination Kits
RXGY-B01	Condensate Pump
RXGY-A01	Neutralizer Kit
RXGC-B17, 21, 24	Non-Combustible Floor Base
RXGJ-FP19, 21	LP Conversion Kits
RXGF-CC	External Filter Rack
RXPF-F01, 02	Fossil Fuel Kits

Warranty Information

Primary and Secondary Heat Exchanger - Limited Lifetime
Any Other Part - Ten (10) Years Conditional Parts Warranty

