



Package Gas / Electric Rooftop Units

RKKA Standard Efficiency Series 3 through 7.5 Tons

Model #	Gross Cooling Capacity BTU/h (Kw)	EER / SEER	Heating Input BTU/h (Kw)	Nominal CFM
RKKA-A036CK08	37,600 (11)	9.4/10.2	80,000 (23.4)	1,200
RKKA-A036KK08E	37,600 (11)	9.4/10.2	80,000 (23.4)	1,200
RKKA-A048CK10E	50,000 (14.6)	9.8/10.4	100,000 (29.3)	1,600
RKKA-A048JK10E	50,000 (14.6)	9.8/10.4	100,000 (29.3)	1,600
RKKA-A060CK13E	63,000 (18.5)	9.3/10.1	135,000 (39.6)	2,000
RKKA-A060JK13E	63,000 (18.5)	9.3/10.1	135,000 (39.6)	2,000
RKKA-A073CL13E	75,000 (22)	9.8/NA	135,000 (39.6)	2,400
RKKA-A085CL13E	90,000 (26.4)	9.1/NA	135,000 (39.6)	2,800

Copeland scroll compressor for maximum reliability, efficiency and quietness. Aluminized steel heat exchanger with in-shot burners helps to eliminated corrosion. Integrated blower/burner control board with built-in diagnostic capability permits on-site trouble shooting. One piece top over the indoor section with drip lip, drawn painted base pan, and 1" raised flanges for supply and return air connections provides superior water management. Convertible horizontal and vertical airflow design allows for field flexibility and minimized inventory needs. Easier to install due to full perimeter forkable 14 gauge baserail with lifting holes. Filter, blower, gas heat, and compressor/control access panels are easy to remove. Number and color coded wiring assists with maintenance. Common cabinet and components allows for installation flexibility and lowers inventory needs. Easy service diagnostic due to externally mounted refrigerant gauge ports. Side and base electric power and gas connection entry helps to minimize roof penetrations. Easy to install plug-in, slip-in 100% fully modulating economizers. Quality powder paint finish offers long lasting protection against extreme weather conditions.

ACCESSORIES		
Model Number	Description	Factory Installation Available
RXKG-BAD14	Roofcurb 14"	No
RXKG-BAD24	Roofcurb 24"	No
RXRX-BBCDB21, 22, 23	Roofcurb Adapters	No
RXRD-KECM3	Economizer with Single Enthalpy	Yes
RXRX-AV02	Dual Enthalpy Kit	No
RXRX-AR02	Carbon Dioxide Sensor Only	No
RXRX-BFF04C	Power Exhaust	No
RXRF-FBA1	Fresh Air Damper Manual	No
RXRF-FBB1	Fresh Air Damper Motorized	No
RXMC-CB03	Rectangular to Round 18" Duct Adapters for Concentric Diffuser	No
RXMC-CB04	Rectangular to Round 20" Duct Adapters for Concentric Diffuser	No
RXRN-FA60	Concentric Diffuser 18" Step	No
RXRN-FA70	Concentric Diffuser 18" Flush	No
RXRN-FA65	Concentric Diffuser 20" Step	No
RXRN-FA75	Concentric Diffuser 20" Flush	No

Model Number	Description	Factory Installation Available
RXMC-BB01	Rectangular to Round 16" Side	No
RXRX-AAD01A	Louver Kit (2 Sides) - For 3 to 6 Ton	Yes
RXRX-AAD01A	Louver Kit (2 Sides) - For 6 to 7.5 Ton	No
RXRX-AAD01B	Louver Kits (3 Sides)	Yes
RXAB-A02	High Pressure Control	Yes
RXAC-A02	Low Pressure Control	Yes
RXMD-B01	Time Delay	Yes
RXRZ-A18	Low Ambient Control Kit	Yes
RXGJ-EP84W	LP Conversion Kits for use with White Rodgers Gas Valve	No
RXGJ-EP85H	LP Conversion Kits for use with Honeywell Gas Valve	No
RXGJ-EP86W	LP Conversion Kits for use with Two-Stage Gas Valve	No

Warranty Information
Heat Exchanger Factory Standard - Ten (10) Years
Stainless Steel 3-Phase Models Commercial Application - Twenty (20) Years
Compressor - Five (5) Years

