



Oil Furnaces

ROBD Classic 80% Upflow Oil Furnaces

Model #	Heating Capacity BTU/h (Kw)	Firing Rate GPH	Dimensions (wx dxh) Inches	Cooling CFM	Blower Diameter (Motor HP)
ROBD-067LBEA	56,000 (16.41)	0.50	21x28 3/4x46	1,140	10X7 (1/4)
	67,200 (19.69)	0.65			
ROBD-112QBGA	84,000 (24.62)	0.75	24 1/2x28 3/4x46	1,375	10X10 (1/2)
	95,200 (27.90)	0.85		1,375	
	112,000 (32.83)	1.00		1,500	
ROBD-150RBJA	134,400 (39.38)	1.20	28x28 3/4x49	2,070	11X10 (3/4)
	151,200 (44.30)	1.35			

Direct drive blower assemblies for heating and air conditioning applications. Crimped design stainless steel heat exchanger for efficient heat transfer. Low profile design is lighter, easier to handle, and replaces old style. Removable flue box to easily clean secondary heat exchanger. Blower/Motor combinations, cooling coil plenums, return air cabinets, and other air conditioning accessories are available for air conditioning application. Factory tested prior to shipment. All furnaces are completely factory assembled with burner mounted ready for operation. Adjustable solid state fan cycle control.

Accessories	Description
RXOP-B25	Parallel Furnace Kit
RXGR-B21B, 24B, 28B	Return Air Cabinets
RXGF-Z16B, 33B	External Side Filter Frames
SS1-R	Sidewall Vent System
RXPF-F01, 02	Fossil Fuel Kits

Warranty Information
Oil Heat Exchanger - Limited Life
Any Other Part - Five (5) Years

