



Heat Pumps

RPNL Classic Series 13 SEER - R410A

Model #	Total Capacity BTU/h (Kw)	Uncased Coil	SEER Rating	Sound Rating	Dimensions (wxdxh) Inches	Line Set Part #	Pad	Voltage	Circuit Amps. Min (Max)
RPNL-018JAZ	18,300 (5.4)	RCSL-H*2417A*	13.0	7.2	27 5/8x40 1/2x19	512	3244	208/230/1	15/15 (20/20)
RPNL-024JAZ	23,400 (6.9)	RCSL-H*2417A*	13.0	7.2	27 5/8x40 1/2x19	512	3244	208/230/1	20/20 (25/25)
RPNL-031JAZ	29,000 (8.5)	RCSL-H*3617A*	13.0	7.3	27 1/2x40 3/8x19	512	3244	208/230/1	25/25 (30/30)
RPNL-036JAZ	38,000 (11.1)	RCSL-H*3617A*	13.0	7.6	31 1/2x44 3/8x33	512	3244	208/230/1	30/30 (40/40)
RPNL-043JAZ	43,000 (12.6)	RCSL-H*4821A*	13.0	7.6	31 1/2x44 3/8x29	614	3244	208/230/1	35/35 (45/45)
RPNL-049JAZ	47,000 (13.8)	RCSL-H*4821A*	13.0	7.6	31 1/2x44 3/8x29	614	3244	208/230/1	35/35 (50/50)
RPNL-060JAZ	60,500 (17.7)	RCSL-H*6024A*	13.0	7.6	31 1/2x44 3/8x33	614	3244	208/230/1	45/45 (60/60)

Attractive wrap around jacket protects coil from the elements. Four sided outdoor coil design allows compressor operation with access panel removed. Air is expelled upward and away from bushes and shrubs, preserving landscaping. The discharge pattern of the top grille provides minimum air restriction, resulting in quiet fan operation. Combination Grille/Motor secures the fan motor to the underside of the discharge grille. All controls are accessible by removing one service panel. Compressor compartment provides additional protection from the elements and reduces operating noise. The single speed, 8 pole fan motor provides a quieter, energy saving operation. The unit also includes a non-cycling reversing valve and demand defrost.

Accessories	Description
RXAD-A07	Low Ambient Control
RXPM-B01	Heat Pump Monitor
RXPT-A01, 02, 03, 04	Outdoor Thermostats
RXMD-B01	Compressor Time Delay Control
RXMD-C04	Blower Time Delay Control
RXPF-01, 02	Fossil Fuel Kits

Warranty Information
Condenser Coil Leaks due to factory defect - Five (5) Years
Compressor A-Series - Ten (10) Years
Compressor B-Series - Seven (7) Years
Any Other Part - Five (5) Years

