



Package Gas / Electric Units

RRKA Standard Efficiency 10 SEER Series 1.5 through 5 Tons RRMA High Efficiency 12 SEER Series 1.5 through 4 Tons

Model #	Gross Cooling Capacity BTU/h (Kw)	EER / SEER	Heating Input BTU/h (Kw)	Nominal CFM
RRKA-A024JK06E	24,800 (7.3)	9.3/10	60,000 (17.6)	800/800
RRKA-A030JK08E	31,200 (9.1)	9.1/10	80,000 (23.4)	1,000/1,000
RRKA-A036JK10E	37,400 (11)	9/10	100,000 (29.3)	1,200/1,200
RRMA-A024JK06E	24,800 (7.3)	10.5/12	60,000 (17.6)	800/800
RRMA-A030JK08E	29,800 (8.7)	10.5/12	80,000 (23.4)	1,000/1,000
RRMA-A036JK10E	37,200 (10.9)	10.6/12	100,000 (29.3)	1,200/1,200

Copeland scroll compressor for maximum efficiency and quietness. One piece top to keep water out. Weep holes to manage water run off. Blower section is easily accessible. Refrigerant connections are easily located. Condenser and evaporator coils are enhanced for better heat transfer. Easily accessible control box. Single point wiring provides easier installation.

Accessories	Description
RXSG-AAA08, 14, 24	Roofcurbs
RXRN-BD15	Supply and Return Diffusers
RXRE-CAA30, RXRD-CAM10	Economizers (Downflow Only)
RXRF-FAB1, A1	Fresh Air Damper
RXMC-CA02, 03	Rectangular to Round Transition (Downflow)
RXRY-B01	Filter Kit
RXRZ-A18	Low Ambient Control
RXAB-A02	High Pressure Control
RXAC-A02	Low Pressure Control
RXMC-BA01	Sideflow Rectangular to Round Transition
RXGJ-EP84W, 85H	LP Conversion Kits

Warranty Information
Factory Heat Exchanger - Ten (10) Years
Factory Option Stainless Steel Heat Exchanger
Three Phase models installed in a commercial application - Twenty (20) Years
Single Phase models installed in a residential application - Limited Lifetime
Condenser Coil and Evaporator Coil leaks due to factory defects - Five (5) Years
Compressor (1 Phase, 12-SEER Models) - Ten (10) Years
Compressor (3 Phase Models) - Five (5) Years
Any Other Part - One (1) Year

