



Package Gas / Electric Units

RRNL Classic Series 13 SEER Series 2 through 5 Tons with R410A Refrigerant

Model #	Gross Cooling Capacity BTU/h (Kw)	EER / SEER	Heating Input BTU/h (Kw)	Nominal CFM
RRNL-B024JK06E	24,400 (7.15)	11.1/13	60,000 (17.58)	787/800
RRNL-B024JK08E	24,400 (7.15)	11.1/13	80,000 (23.44)	787/800
RRNL-B030JK08E	29,800 (8.73)	11.1/13	80,000 (23.44)	953/1,000
RRNL-B036DK10E	37,000 (10.84)	11.3/13	100,000 (29.3)	1,187/1,200
RRNL-B036JK08E	37,000 (10.84)	11.3/13	80,000 (23.44)	1,187/1,200
RRNL-B048CK10E	50,000 (14.65)	11.2/13	100,000 (29.3)	1,600/1,600
RRNL-B048JK10E	50,000 (14.65)	11.2/13	100,000 (29.3)	1,600/1,600
RRNL-B060CK10E	59,500 (17.43)	10.5/13	100,000 (29.3)	2,000/1,850
RRNL-B060JK10E	59,500 (17.43)	10.5/13	100,000 (29.3)	1,900/1,850

Scroll compressor for maximum efficiency and quiet operation. Louvered condenser compartment to protect the coil from yard hazards and weather extremes. One piece top with a deep flange to help keep water out of unit. Supply and return air openings feature a one inch tall flange to prevent water migration into the ductwork. Access panels have weep holes and channels to further help manage water run off. All models have side and down discharge options. Blower section is easily accessible, with slide out blower. Refrigerant connections are conveniently located for easy service diagnostics. Condenser and evaporator coils feature enhanced fins for better heat transfer and rifled copper tubing for greater efficiency. Easily accessible furnace compartment. Specially designed motor for quiet and reliable operation. The draft inducer motor, in-shot gas burners and manifold efficiently regulate the flow of gas for combustion. Direct spark ignition and remote flame sensor for added reliability and efficiency. Internal trap on the condensate line. Easily accessible control box. Single point wiring makes installation easier. Tubular heat exchanger is more durable and efficient than clamshell heat exchangers. Thermal expansion valve for superior superheat control, reliability, and energy efficiency at all operating conditions. Filter drier standard. Rugged baserail for improved handling and installation.

Accessories	Description
RXSG-AAA08, AAA14, AAA24	Roofcurb
RXRN-BD15	Supply and Return Diffuser
RXRE-CAA30, RXRD-CAM10	Economizer (Downflow Only)
RXRE-CCA30, RXRD-CCM10	Economizer (Sidelflow Only)
RXRF-FAB1, FAA1	Fresh Air Damper
RXMC-CA02, CA03	Rectangular to Round Transition (Downflow)
RXRY-B01	Filter Kit
RXRZ-B01	Low Ambient Control
RXAB-E01	High Pressure Control
RXAC-C01	Low Pressure Control
RXMC-BA01	Sidelflow Rectangular to Round Transition
RXGJ-EP84W, EP85H	LP Conversion Kit

Warranty Information

Heat Exchanger:

Factory Standard - Ten (10) Years

Stainless Steel Single and Three Phase Models, Commercial Application - Twenty (20) Years

Stainless Steel Single Phase Models, Residential Application - Limited Lifetime

Condenser Coil and Evaporator Coil leaks due to factory defects - Five (5) Years

Compressor:

Single and Three Phase Models, Commercial Application - Five (5) Years

Single Phase Models, Residential Application - Ten (10) Years

Any Other Part:

Single Phase Models, Residential Application - Five (5) Years

Single and Three Phase Models, Commercial Application - One (1) Year

