



Unit Heaters

UDAP Series V3 Power Vent

Model #	Heating Input BTUH (Kw)	Thermal Output BTUH (Kw)	Vent Outlet Diameter (inches)	Standard Motor HP open (enclosed)	Air Volume CFM	Approximate Shipping Weight lbs (kg)
UDAP 30	30,000 (8.8)	24,600 (7.2)	4	0.02 (NA)	456	61 (27)
UDAP 45	45,000 (13.2)	37,350 (11.0)	4	0.03 (NA)	629	66 (30)
UDAP 60	60,000 (17.6)	49,800 (14.6)	4	0.03 (NA)	769	74 (33)
UDAP 75	75,000 (22.0)	62,250 (18.3)	4	0.06 (NA)	961	79 (36)
UDAP 100	105,000 (30.8)	87,150 (25.6)	4	1/30 (1/4)	1,345	118 (54)
UDAP 125	120,000 (35.2)	99,600 (29.2)	4	1/20 (1/4)	1,537	123 (56)
UDAP 150	150,000 (43.9)	124,500 (36.4)	5	1/6 (1/4)	1,921	172 (78)
UDAP 175	175,000 (51.2)	145,250 (42.5)	5	1/6 (1/4)	2,242	187 (85)
UDAP 200	200,000 (58.6)	166,000 (48.6)	5	1/6 (1/4)	2,562	187 (85)
UDAP 225	225,000 (65.9)	186,750 (54.7)	5	1/4 (1/4)	2,882	203 (92)
UDAP 250	250,000 (73.2)	207,500 (60.8)	5	1/4 (1/4)	3,202	215 (98)
UDAP 300	300,000 (87.8)	249,000 (72.9)	6	1/2 (1/2)	3,843	269 (122)
UDAP 350	350,000 (102.5)	290,500 (85.1)	6	1/2 (1/2)	4,483	294 (133)
UDAP 400	400,000 (117.1)	332,000 (97.2)	6	1/2 (1/2)	5,123	306 (139)

Integrated circuit board with diagnostic indicator lights, fan relay, multi-try direct spark ignition with 100% lockout, single stage natural gas valve, vibration/noise isolated fan and venter motors, external terminal strip, external gas connections, full fan guard. Patented V3 technology of the Tcore combustion system provides up to 83% efficiency.

Accessories	Description
Option AC2	409 SS Heat Exchanger
Option AG2	Two-Stage Gas Control
Option CD2	25-65 Degree Variable Air Deflection
201727-32	LP Conversion Kits



Warranty Information

For the original owner-user the Reznor unit will be free from defects in materials or workmanship. This warranty is limited to twelve (12) months from the date of the original installation, whether or not actual use begins on that date or eighteen (18) months from date of shipment by Reznor, whichever comes first. Extended nine (9) year non-prorated warranty on the heat exchanger, burners, drafthood and flue battle assembly. Extended four (4) year non-prorated warranty on all electrical and mechanical operating components.

